



The Mulching Specialists



Twister II **C175**



MULCHING
is the **ECOLOGICAL SOLUTION**

Twister II **C175**

The C175 is a versatile machine. Offered with two mulcher head sizes, it is ideal for seismic applications, commercial land clearing, trail & road right-of-ways and other mulching applications. The C175 has an ideal weight to permit hauling without requiring a large transport.



MACHINE

A - Overall Length: 228.5 inches (580 cm)

B - Ground Clearance: 18.75 inches (47 cm)

C - Overall Height: 100 inches (254 cm)

D - Overall Tractor Width: 68 inches (173 cm)

MULCHER** (140-U140, Optional Tilt)

E - Overall Width Attachment: 70 inches (177 cm)

F - Working Width: 55 inches (140 cm)

G - Overall Height (pushbar fully retracted): 61 inches (155 cm)

** Optional mulcher head 140-U 200 available

Specifications

ENGINE

Manufacturer & Model: John Deere, 4045T

Non-Road Emission Standard: EPA Tier 3

Cylinders/Displacement: 4 cylinders/276 cu. In (4.5 L)

SAE Net Rated Power at 2,500 rpm: 173 Hp (129 Kw)

Net Peak Torque @ 1,400 rpm: 476 Lb.-Ft. (645 Nm)

Air Cleaner: Precleaner & 2 stage air cleaner, dry type

Fan: Automatic variable pitch, reversible

HYDRAULICS

Number of pumps: 4

Attachment: One piston pump

Track: Two piston pumps

Auxiliary function: One gear pump

Filtration: 10 micron screens on charge pumps.

25 micron screens on all other pumps and motors

ELECTRICAL

Voltage: 12 volts

Battery Capacity: 950 CCA

Alternator: 120 Ah

Standard Light: 8 Halogen type (4 Front, 2 Side, 2 Rear)

UNDERCARRIAGE & GROUND PRESSURE

Chain Type & Size: Dry, FL4 type

Rollers, Bottom: 8 single and double flange tractor type

Roller, Upper: 1 single flange

Track Shoe: 18 in. (457 mm) single grouser with mud hole

Ground Pressure with Mulcher Head: 4.4 Psi (0.31 kg/cm²)

Ground Pressure Crawler Tractor only: 3.6 Psi (0.25kg/cm²)

Weight (Crawler & Mulcher): 16,500 lbs (7,485 kg)

Weight (Crawler only): 13,535 lbs (6,153 kg)

SERVICEABILITY

Fuel Tank: 76 gal. (290 L)

Hydraulic Reservoir: 32 gal. (121 L)

Cooling System: 6.5 gal. (24.6 L)

WINCH

Standard: 15,000 lbs (6,800 kg)

TOP SPEED

Motor: Two speed hydraulic motors

Speed: Variable speed from 0 to 3.7 mph (0 to 6.0 km/h)

C.M.I. reserves the right to change specifications, design and price of products described in this literature without notice. C.M.I. and Twister II C175 are registered trademarks of C.M.I. Danri inc. Printed in Canada.